

## Beer Showcase Technical Features

		MODEL	LG138	LG208H	LG208S	LG330H	LG330S
System	Net (Liters)	138	208	208	330	330	330
	Net (CB FEET)	4,9	7,3	7,3	11,7	11,7	11,7
	Cooling system	Fan cooling	Fan cooling	Fan cooling	Fan cooling	Fan cooling	Fan cooling
	Auto-Defrost	Yes	Yes	Yes	Yes	Yes	Yes
	Control system	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Dimensions	External Dimension WxDxH(mm)	600*520*900	900*520*900	900*520*900	1350*520*900	1350*520*900	1350*520*900
	Internal Dimension WxDxH(mm)	520*385*750	820*385*750	820*385*750	1260*385*750	1260*385*750	1260*385*750
	Packing Dimension WxDxH(mm)	650*570*980	960*570*980	960*570*980	1405*570*980	1405*570*980	1405*570*980
	Weight net /Weight gross (kg)	48/58	62/72	62/72	80/90	80/90	80/90
	20'GP/ 40' GP/ 40' HQ Container	72/144/144	48/96/96	48/96/96	32/66/66	32/66/66	32/66/66
Doors	Glass Door type	Hinge door	Hinge door	Sliding door	Hinge door	Sliding door	Sliding door
	Door frame, door handle material	PVC	PVC	PVC	PVC	PVC	PVC
	Glass type, (tempered)*	TEMPERED GLASS	TEMPERED GLASS	TEMPERED GLASS	TEMPERED GLASS	TEMPERED GLASS	TEMPERED GLASS
	Door Auto Closing	Auto Closing	Auto Closing	Auto Closing	Auto Closing	Auto Closing	Auto Closing
	LOCK	YES	YES	YES	YES	YES	YES
Insulation (CFC-free)	Type	R141b	R141b	R141b	R141b	R141b	R141b
	Dimensions (mm)	40(average)	40(average)	40(average)	40(average)	40(average)	40(average)
Equipment	Adjustable shelves (pcs)	2	4	4	6	6	6
	Adjustable feet (pcs)	4	4	4	4	4	4
	Locking Feet	0	0	0	0	0	0
	Internal light vert./hor.*	Horizontal*1	Horizontal*1	Horizontal*1	Horizontal*1	Horizontal*1	Horizontal*1
Specification	Voltage/frequency	220~240V/50HZ	220~240V/50HZ	220~240V/50HZ	220~240V/50HZ	220~240V/50HZ	220~240V/50HZ
	Power consumption (w)	180	230	230	265	265	265
	Amp. Consumption (A)	1	1,56	1,56	1,86	1,86	1,86
	Energy consumption (kWh/24h)	1,5	1,9	1,9	2,5	2,5	2,5
	Cabinet Tem. °C	4~8 °C	4~8 °C	4~8 °C	4~8 °C	4~8 °C	4~8 °C
	Temperature digital screen	Yes	Yes	Yes	Yes	Yes	Yes
	Climate Class As per EN441-4	Class 3 □ 4	Class 3 □ 4	Class 3 □ 4	Class 3 □ 4	Class 3 □ 4	Class 3 □ 4
	Max. Ambient Temp. °C	32 °C	32 °C	32 °C	32 °C	32 °C	32 °C
Components	Refrigerant (CFC-free) gr	R134a /75g	R134a /125g	R134a /125g	R134a /185g	R134a /185g	R134a /185g
	Outer Cabinet	Pre-painted steel	Pre-painted steel	Pre-painted steel	Pre-painted steel	Pre-painted steel	Pre-painted steel
	Inside Cabinet	Compressed aluminium	Compressed aluminium	Compressed aluminium	Compressed aluminium	Compressed aluminium	Compressed aluminium
	Condenser	Bottom Mash Wire	Bottom Mash Wire	Bottom Mash Wire	Bottom Mash Wire	Bottom Mash Wire	Bottom Mash Wire
	Evaporator	Blow expanded board	Blow expanded board	Blow expanded board	Blow expanded board	Blow expanded board	Blow expanded board
	Evaporator fan	14W Square fan	14W Square fan	14W Square fan	14W Square fan	14W Square fan	14W Square fan
	Certification	CE,ROHS,GS	CE,ROHS,GS	CE,ROHS,GS	CE,ROHS,GS	CE,ROHS,GS	
Pictures							